

CITIZEN® Low-cost Label Printers

CBM-270L, CBM-1000L-II



CBM-270L



CBM-1000L-II

CBM-270L and CBM-1000L-II are low-cost label printers designed for a wide variety of business applications including receipt printing. CBM-1000L-II has a built-in auto cutter



Easy paper loading
Just drop a paper in and close the top cover.

Specifications

Model	CBM-270L	CBM-1000L-II
Print technology	Direct Thermal	Direct Thermal
Print speed	max. 30 mm / sec	max. 100 mm/sec.
Print resolution	203 dpi	203 dpi
Paper width	58 mm	58 mm or 80 mm
Print width	48 mm	54 mm (58 mm paper) or 72 mm(80 mm paper)
Max. length	300mm (label length) 296.2 mm (print length)	360.0 mm (label length) 356.0 mm (print length)
Mini. length	25.0 mm (label length) 21.0 mm (print length)	25.0 mm (label length) 21.0 mm (print length)
Paper thickness	~ 0.150 mm	0.140 mm ~ 0.160 mm
Media detection sensor	Fixed sensor	Fixed sensor
Barcode types	UPC-A/E, JAN(EAN), ITF, CODABAR, CODE 39 CODE 128	UPC-A/E, JAN(EAN), ITF, CODABAR, CODE 39 CODE 128
Font size	Font A : 1.25 x 3.00mm (12 x 24 dots), Font B : 0.88 x 3.00mm (9 x 24 dots)	Font A : 1.25 x 3.00mm(12 x 24 dots), Font B : 0.88 x 3.00mm (9 x 24 dots)
Input buffer	2 Kb	4 Kb
Standard interfaces	RS-232C serial or Centronics parallel	RS-232C serial or Centronics parallel
Power supply	110 or 220 VAC	110 or 220 VAC
Operating environment	5°C ~ 40°C, Humidity 30 ~ 85% (non-condensing)	5°C ~ 40°C, Humidity 30 ~ 85% (non-condensing)
Outer structure	Plastic case	Plastic case
Dimensions (mm)	106 mm (W) x 110 mm (H) x 184 mm (D)	145 mm (W) x 157 mm (H) x 197 mm (D)
Weight	0.6 kgs	2.2 kg

All specifications are subject to change without notice

Japan CBM Corporation

Information Systems Division
5-68-10 Nakano, Nakano-ku, Tokyo, 164-0001 Japan
Tel: (81)-3-5345-7540
Fax: (81)-3-5345-7541
<http://www.jcbm.co.jp/>
e-mail: info-sys@jcbm.co.jp

Printed in Japan