

# Epson TM-C3500



## Product Specifications

<b>PRINT METHOD</b>	MicroPiezo® inkjet technology, Automatic Nozzle Checking technology
<b>INK TYPE</b>	Epson DURABrite® Pigment Ink, individual CMYK cartridges
<b>PRINT RESOLUTION</b>	360 dpi x 360 dpi – Speed Mode, 720 dpi x 360 dpi – Quality Mode
<b>PRINT SPEED (max.)</b>	360 dpi x 360 dpi – Banding Reduction disabled - 103mm/sec (56mm print width) - 85mm/sec (104mm print width) 360 dpi x 360 dpi – Banding Reduction enabled - 95mm/sec (56mm print width) - 78mm/sec (104mm print width) 720 dpi x 360 dpi – Banding Reduction enabled - 52mm/sec (56mm print width) - 42mm/sec (104mm print width)
<b>PRINT WIDTH</b>	Max. 104 mm
<b>MEDIA TYPES</b>	Roll-fed or fanfold; die cut or continuous; single layer or adhesive labels on liner; plain paper, fine paper, PET film, synthetic, glossy
<b>MEDIA DIMENSIONS</b>	
<b>Width</b>	
	30 – 108mm (roll feed) 50 – 108mm (fan fold)
<b>Thickness</b>	
	0.12-0.19mm (plain/matte/synthetic labels) 0.184mm (glossy label)
<b>Roll size</b>	
	Outer diameter: 102mm max. Core diameter: 44.1 mm or more (plain/matte/synthetic labels), 56.8mm or more (glossy labels)
<b>MEDIA SENSORS</b>	
	Gap, black mark, media cut
<b>Die cut label gap</b>	3 to 6mm
<b>Black mark size</b>	
	Width of a black mark: 13mm or more Length of a black mark : 5mm or more
<b>INTERFACES</b>	
	USB 2.0 High-speed, Ethernet 100BASE-TX /10BASE-T
<b>OPERATING SYSTEM</b>	
	Microsoft® Windows® XP 32-bit (SP3)/64-bit (SP2), Vista® 32-bit/64-bit (SP2), Windows 7 32-bit/64-bit (SP1), Windows 8 32-bit/64-bit
<b>BARCODES (Built-in driver)</b>	
	Barcodes: UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded. 2-dimensional symbols: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Composite Symbology, DataMatrix, Aztec
<b>MTBF</b>	88,000 hours
<b>MCBF</b>	9.8 million lines
<b>POWER CONSUMPTION</b>	
	30W Printing (average printing) 2.5W Standby 0.3W Power Off state
<b>RATED VOLTAGE</b>	AC 100-240V
<b>RATED FREQUENCY</b>	50-60Hz
<b>EMI</b>	C-Tick Class B
<b>SAFETY STANDARDS</b>	UL / CSA / TÜV (EN60950-1)
<b>ACOUSTIC NOISE</b>	Approx. 58 dBA
<b>MAIN UNIT DIMENSIONS</b>	310 (W) x 283 (D) x 261 (H) mm
<b>MAIN UNIT WEIGHT</b>	Approximately 12 kg

<sup>1</sup> Inkjet cartridge yields vary considerably for reasons including item printed, print settings, temperature and humidity. Yields may be lower when printing infrequently. A variable amount of ink remains in the cartridge after the "replace cartridge" signal. Ink from the first cartridge is used for priming the printer. Ink is used for both printing and print head maintenance.

Better Products for a Better Future

**EPSON**  
EXCEED YOUR VISION