

Specifications SRPF310UEG

Printing Method	Thermal Line Dot method
Print Speed	Max. 270 mm/sec
Resolution	180 Dpi (7 dot/mm) (203Dpi available, special order only) Font A: 42 Columns
Column Capacity	Font B: 56 Columns Font C: 56 Columns Alpha Numeric Character: 95
Character Set	Extended Graphics: 128 X 33 (1 Space Page) International Characters: 32
Character Size	Font A: 12 x 24 dots Font B: 9 X 17 dots Font C: 9 X 24 dots
Emulation	ESC/POS™
Drivers	Windows™ Driver, OPOS Driver, JPOS Driver, Linux CUPS Driver, MAC Driver
Bar-code type	1D: UPC-A/E, EAN-13/8, ITF, Code 39, Code 128, CODABAR, Code 93 2D: PDF417, QR-Code
Input Buffer	4 Kb
NV Bitmap Memory	256 Kb
Sensors	Paper near end, Paper end, Cover open
	Serial RS-232C
	Unidirectional Parallel IEEE 1284
Interface	USB USB 2.0 (fitted as standard) Ethernet (fitted as standard) WLAN (using RWD100 Dongle)
Paper Width	80/83 mm
Paper Roll max. Ø	105 mm
Drawer Kick-out	2 drawers through 1 RJ12 Connector
Power	AC 100~240V / 24 DCV +/- 7%, 2.5A, Internal power Supply
Operating Temperature	0 ~ 45 °C
External Dimensions (WxDxH)	154 x 203 x 148 mm