

SPECIFICATIONS

Printer	TTP-245C	TTP-343C	TTP-244CE
Resolution	203 DPI	300 DPI	203 DPI
Printing method	Thermal Transfer & Direct Thermal		
Print speed	Up to 6 ips	Up to 4 ips	Up to 4 ips
Max. print width	108 mm (4.25")	106 mm (4.17")	108 mm (4.25")
Max. print length	2,286 mm (90")	1,016 mm (40")	2,286 mm (90")
Enclosure	Double-walled plastic		
Physical dimension	258 mm (L) x 202 mm (W) x 173 mm (H) 10.16" (L) x 7.95" (W) x 6.81" (H)		
Label roll capacity	127 mm (5") OD		
Ribbon capacity	110 meter, Max. 40 mm (1.57") OD, 12.7 mm (0.5") core		
Processor	32-bit RISC CPU		
Memory	<ul style="list-style-type: none"> • 2 MB FLASH memory • 8 MB SDRAM • SD card slot for memory expansion 		<ul style="list-style-type: none"> • 2 MB FLASH memory • 8 MB SDRAM
Interface	<ul style="list-style-type: none"> • RS-232C • Centronics • USB 2.0 (full speed mode) • Internal Ethernet 		<ul style="list-style-type: none"> • USB 2.0 (full speed mode)
Power	External universal switching power supply		
Operation switch, button, LED	<ul style="list-style-type: none"> • One power switch • One feed button • One LED (3 colors: Green, Amber & Red) 		
Sensors	<ul style="list-style-type: none"> • Gap transmissive sensor • Moveable black mark reflective sensor • Head open sensor • Ribbon end sensor 		
Internal font	<ul style="list-style-type: none"> • Eight alpha-numeric bitmap fonts • One Monotype® Imaging CG Triumvirate Bold Condensed scalable font • Built-in Monotype® True Type Font engine 		
Bar code	1D bar code Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET 2D bar code PDF-417, Maxicode, DataMatrix, QR code		
Font & barcode rotation	0, 90, 180, 270 degrees		
Printer language	TSPL-EZ™		
Media type	<ul style="list-style-type: none"> • Continuous, die-cut, tag & fan-fold • Linerless (DT only) 		<ul style="list-style-type: none"> • Continuous, die-cut, tag & fan-fold
Media wound type	Outside wound		
Media width	25.4~112 mm (1.0"~ 4.4")		
Media thickness	0.06~0.19 mm (2.3~7.4 mil)		
Media core diameter	25.4 mm (1") & 38.1 mm (1.5")		
Environment condition	Operation: 5~40°C (41~104°F), 25~85% non-condensing Storage: -40~60°C (-40~140°F), 10~90% non-condensing		
Safety regulation	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/GS, CCC		
Accessories	<ul style="list-style-type: none"> • BarTender UltraLite labeling software/Driver CD disk • Quick start guide • USB cable • External universal switching power supply • Power cord 		
Factory option	<ul style="list-style-type: none"> • Real time clock 		N/A
Dealer option	<ul style="list-style-type: none"> • Peel off module assembly • Guillotine cutter • Linerless kit (including linerless cutter & linerless platen) 		N/A
User option	<ul style="list-style-type: none"> • Keyboard display unit (KU-007 Plus and KP-200) • Contact CCD bar code scanner • Long range linear image bar code scanner • External wireless (802.11b/g) print server • External media hanger with 3" OD label spindle 		<ul style="list-style-type: none"> • External wireless (802.11b/g) print server • External media hanger with 3" OD label spindle