

QuickScan® QS6500BT

Linear Imager Featuring **Bluetooth®** Wireless Technology

Data Sheet



Features:

- Aggressive linear imaging performance with 450 scans per second
- Bluetooth certified wireless communication with 30' / 9.1 m range
- Upright charging cradle position enables hands-free scanning
- Out of range anti-theft alarm
- Durable design is built tough to withstand common abuse for many years
- Flash memory for easy software upgrades
- Multi-interface base station supports all popular host terminal interfaces
- Supports RSS and PDF-417 for future industry compatibility
- Batch mode allows items out of range to be scanned
- User replaceable battery

Mechanical

Dimensions	Scanner	Base Station
Height	18.0 cm / 7.1"	7.4 cm / 2.9"
Width	7.4 cm / 2.9"	9.4 cm / 3.7"
Length	11.2 cm / 4.4"	15.5 cm / 6.1"
Weight	226.8 g / 8.0 oz	340.2 g / 12.0 oz

Environmental

Temperature Rating

Operating: 32° to 122° F / 0° to 50° C

Storage: -40° to 158° F / -40° to 70° C

Humidity

Operating: 5 to 95% NC

Storage/Transport: 5 to 95% NC

Shock

Withstands multiple 1.5 m / 5' drops to concrete

Vibration: Meets MIL STD-810E

Water & Dust: IEC 60529 rating IP52DW

Electrical

Operating Voltage: +4.5 to 14VDC ±5%

Current

Operating: 220mA @ 5VDC or 120 mA @ 10V

Charging: 1,200mA @ 5VDC or 480 mA @ 10V

Battery: Li-Ion 1,000 mAh, User replaceable

Charge: via Cradle, full charge in 3.5 hours

Optical

Ambient Light Immunity

Artificial & Sunlight: 80,000 Lux

Light Source: 630nm Visible Red Diode

Scan Rate: 450 scans/sec max

Sensor: 2048 pixel linear imager

Scan Width: 16.5 cm / 6.3" @ 178 cm / 7' from nose

Depth of Field: Refer to Chart below

Resolution: .13 mm / 5 mils

Print Contrast: 30% or greater

Pitch: ±60°

Skew: ±55°

DEPTH OF FIELD Range Comparisons	
LABEL DENSITY	RANGE*
5 mils	5 - 11.4 cm / 2.0 - 45"
75 mils	2.5 - 16.2 cm / 10 - 60"
10 mils	0 - 26.7 cm / 0 - 105"
13 mils / 100% UPC	0 - 33 cm / 0 - 13"
20 mils	53.3 cm / Up to 21"
40 mils	89 cm / Up to 35"

* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Wireless Communications

Protocol: Bluetooth 1.2 certified Class 2

Frequency: 2.4 GHz Spread Spectrum with Adaptive Frequency hopping

Range: Class 2: up to 10 m / 30'

Host Communications

- RS-232
- Keyboard Wedge
- IBM 46XX
- IBM USB
- USB
- Wand Emulation

Decoding Capability

- UPC A, E / EAN 8, 13 / JAN 8, 13 Add-ons (sub 2 or P2, sub 5 or P5 & C128)
- Codabar/NW7
- Code 11
- Code 16K
- Code 93
- Code 128
- UK/Plessey
- MSI/Plessey
- Code 39 (full ASCII)
- RSS-14, Expanded, Stacked, Limited
- ISBN / Bookland EAN
- Pharmacode 39
- Interleaved 2 of 5
- Standard 2 of 5
- IATA

- PDF-417
- Micro-PDF
- RSS Composites

Safety & Regulatory

Electrical: Complies to: Gost R; UL; cUL; IEC60950

Emissions: Complies to: FCC-A; EN 55022-B; CISPR-22; VCCI-B

Radio: FCC Part 15C, R and TTE, IC and IDA.

For RF Approved countries, please contact PSC.

Laser Classification: IEC 60825 Class 1 LED



PSC Inc.
959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140

www.psc.com



The **Bluetooth®** word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by PSC Inc. is under license.



Copyright © PSC Inc. 2006. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from PSC. PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. PSC, the PSC logo, and QuickScan are registered trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. Product specifications are subject to change without notice.

