

# SRP-275III

3 inch Impact Dot POS Printer



Retail



Hospitality




Banking



Ticketing

# Simply Drop-in



### Built-in Interface

- USB + Ethernet + Serial
- USB + Parallel



**2-color**

### Powerful Printing Performance

- Fast printing speed up to 5.1 lps (at 40 columns) 8.5% faster than competitive models
- High reliability mechanism (1.8 Million Cuts)
- Two-color printing, quality printing of fonts, graphics



### User-friendly Design

- Anti-jam technology
- Internal kitchen buzzer & built - in SMPS
- Simply drop-in paper loading
- Stand-alone and wall-mount option



# SRP-275III

3 inch Impact Dot POS Printer

## Specifications

### Print Characteristics

#### Print Method

9 Pin  
Serial Dot Matrix

#### Print Speed

5.1 lps (at 40 columns)

#### Print Resolution

80 dpi (horizontal)  
144 dpi (vertical)

#### Print Width

Up to 63.5 mm

#### Sensor

Paper End, Paper Near End, Wall Mounting Paper  
Near End, Rear Cover Open, Black Mark

### Media Characteristics

#### Media Type

Receipt

#### Media Width

76.5 mm

#### Media Roll Diameter

Up to 83 mm

#### Media Thickness

0.06 ~ 0.085 mm

#### Supply Method

Easy Paper Loading

### Physical Characteristics

#### Dimensions (WxLxD)

160 x 239 x 157 mm  
(6.29 x 9.40 x 6.18 inch)

#### Weight

A: 2.4 kg (5.29 lbs.)  
C: 2.5 kg (5.51 lbs.)

#### Power

EnergyStar Certified,  
External Power Adaptor 100-240V AC, 50/60Hz

#### Drawer Port

2 ports (via y-type adaptor)

### Performance Characteristics

#### Memory

64 Mbit SDRAM, 16 Mbit FlashROM

#### NV Image Memory

256 Kbytes (mono)

#### Receive Buffer

64 Kbytes

#### User Define Buffer

64 Kbytes

#### Interface

Max. Triple Interface  
USB V2.0 FS + Serial + Ethernet\*  
USB V2.0 FS + Parallel  
\* DHCP enabled

### Environment Characteristics

#### Temperature

Operating: 0 ~ 40°C (32 ~ 104°F)  
Storage: -20 ~ 60°C (-4 ~ 140°F)

#### Humidity

Operating: 10 ~ 80% RH  
Storage: 10 ~ 90% RH

### Reliability

#### Thermal Print Head (TPH)

300 Million Dots/Wire

#### Auto Cutter

1.5 Million Cuts

### Software

#### Emulation

BXL / POS

#### Driver / Utility

Windows Driver, OPOS Driver, JPOS Driver,  
Linux / Mac CUPS Driver,  
Virtual COM USB/Ethernet Driver, Utility Program

#### SDK

iOS SDK, Android SDK

### Fonts / Graphics / Symbologies

#### Character Size

Font A: 9 x 9 Font B: 7 x 9 KOR: 17 x 9 CHN: 16 x 16

#### Characters Per Line

Font A: 35 Font B: 40 KOR: 20 CHN: 22

#### Character Sets

Alphanumeric: 95  
Extended Graphics: 128 x 27 page  
International: 48

#### Graphics

Supporting user-defined fonts, graphics, formats,  
and logos

### Accessories

#### Optional

Wall Mount (RWM-350)  
Splash Proof Cover (RSC-275)  
Ribbon Cartridge (GRC-201B/GRC-201BR)  
B-Melodist (RMB-100)  
External Buzzer (RBC-100)

